

---

# Fondamenti della Programmazione: Metodi Evoluti

Prof. Enrico Nardelli

Esercitazione 2

A first project: a bank account

Practice debugging: the most important issue!

## Remember: Eiffel Naming Conventions

---

- Full words, no abbreviations (with some exceptions)
- Locals and arguments share namespace with features
  - Name clashes arise when a feature is introduced, which has the same name as a local (even in parent)
- To prevent name clashes:
  - Locals are prefixed with **l\_**
  - Arguments are prefixed with **a\_**
- But exceptions may exist...

## Remember: Editor shortcuts

---

- Auto-completion (CTRL+Space)
- Class name completion (CTRL+SHIFT+Space)
- Block indenting or unindenting (TAB and SHIFT+TAB)
- Block commenting or uncommenting (CTRL+K and SHIFT+CTRL+K)
- Quick search features (first CTRL+F to enter words then F3 and SHIFT+F3)
- Pretty printing (CTRL+SHIFT+P)
- Editor line numbering (Tools -> Preferences -> check "Include Values" -> Search -> Filter insert 'line' -> Editor.General.Show line numbers -> double click on 'False')

# An example: modeling a bank account

---

What do we need to represent?

DATA:

- the fact that the account is open or closed
- which is its balance

OPERATIONS:

- open the account
- close it
- deposit an amount on it
- withdraw an amount from it
- know its balance

FUNDAMENTAL RULE OF SW DEVELOPMENT:

**Enable people reading the code to understand it**

## Features: Exercise

- Assume class *BANK\_ACCOUNT* defines the following operations:  
(will be developed in the next practice session)
  - *deposit (i: INTEGER)*
  - *withdraw (i: INTEGER)*
  - *close*
  
- If *b: BANK\_ACCOUNT* (*b* is an instance of class *BANK\_ACCOUNT*) which of the following feature calls are possible:
  - *b.deposit (10)* ✓
  - *b.deposit* ✗
  - *b.close* ✓
  - *b.close ("Now")* ✗
  - *b.open* ✗
  - *b.withdraw (100.50)* ✗
  - *b.withdraw (0)* ✓

## Exercise: query or command?

---

- To know the balance of a bank account
- To withdraw some money from a bank account
- To know who is the owner of a bank account
- To know the clients of a bank whose deposits are over 100,000 euros
- To change the account type of a client
- To know how much money can a client withdraw at a time
- To set a minimum limit for the balance of accounts
- To know whether Bill Gates is a client of Credit Suisse

# A first attempt for BANK\_ACCOUNT

---

feature -- state

open: BOOLEAN

-- the account is open

balance: INTEGER

-- how much money is in the account

feature -- operation

withdraw (a\_sum: INTEGER)

-- withdraw `a\_sum' from the account

deposit (a\_sum: INTEGER)

-- deposit `a\_sum' from the account

feature -- management

close

-- close the account

start

-- open the account



# Debugger: setup

---

- Setting and unsetting **breakpoints**
  - An efficient way consists of dropping the feature you want the breakpoint in into the context tool.
  - Alternatively, you can select the flat view.
  - Then click on one of the little circles in the left margin to enable/disable single breakpoints.
- Use the toolbar debug buttons to enable or disable all breakpoints globally.
- The system must be melted/frozen (finalized systems cannot be debugged).

## Debugger: run

---

- Run the program by clicking on the Run button.
- Pause by clicking on the Pause button or wait for a triggered breakpoint.
- Analyze the program:
  - Use the **call stack pane** to browse through the call stack.
  - Use the **object tool** to inspect the current object, the locals and arguments.
- Run the program or *step over* (F10) / *into* (F11) the next statement, or *out* (↑F11) of the current one
- Stop the running program by clicking on the Stop button.